

The Basics



Check Line Weight. Make sure free-floating lines are 0.6pt minimum. (0.2 mm)



Make sure all fonts are converted to outlines or shapes.



Save as PDF (Ideally from vector files)

Detailed Specifications.

The Essentials

Use CMYK color mode



CMYK is the color format used for physical print. Files in RGB mode will be converted, which may result in different colors than desired.

Avoid thin free-floating lines



Setting small elements to at least 0.2mm thick ensures every last detail gets printed, and nothing disappears.

Keep at Full Opacity



All semi-transparent effects, such as glows, fades and shadows, must be encased by something solid, with hard edges.

Vector Specifics



Convert Text to Shapes

Editable text objects in your file may not come out correctly. Convert all text to shapes or outlines to guarantee your typography comes out exactly the way you want it.



Embed Linked Images

Any files linked in your artwork will be non-existent on our end. To ensure they come through in print, embed them into the main art file. Alternatively, save your artwork as a PDF (using High Quality Print settings).



Remove Custom Spot Colors

Our printer may interpret these incorrectly, resulting in an undesired color. Make sure the only swatches in your file are official Pantone Solid Coated colors to ensure correct color matching.

Note: Some specialty colors such as neons, pastels and premium metallic cannot be matched, and Pantones made for uncoated paper, textiles, etc, are not suitable for our process. Pantone color matches should always end with C.



Expand Pattern Fills

As part of the artwork preparation process, our team often needs to move artwork around. If a pattern fill is used in a design, it may come out offset if it isn't expanded first, so make sure you expand any pattern fills before supplying your file.

Raster Specifics



Transparent Background

A transparent background on your art file ensures that everything that's supposed to be clear remains unprinted and is not unexpectedly filled with white (or another background color). If you have a transparent background, save your file as a PNG or PSD file.

Note: Do not provide a JPG file if you have any transparent sections, as these sections will print white. Only use JPGs if you're printing a full rectangular image with no transparent parts.



High Resolution Images

To print crystal-clear detail, we recommend art files have a resolution of at least 300 PPI (pixels per inch). For best results, set your document to 800 PPI before you start creating your design.

e.g. a 10-inch-wide transfer should be at least 3,000 pixels wide. Artwork at 8,000 pixels wide will provide optimal results.

Still not sure if your art is print-ready?
Flick us an email at hello@supacolor.com
we'd be happy to check it for you.

Supported File Types.

